

## Highlights:

---

- 500 Watt program power
- Low frequency extension down to 36Hz without processing
- Precision with immersive infra-sub performance
- Tailor-made high excursion 8" aluminum driver for superior outdoor performance
- Vibration-cancelling 10" aluminum passive radiator
- Vibration-decoupled mounting system
- Architecturally discreet and compact design
- Flexible ceiling & wall mount option
- MarineGrade build quality with aluminum housing - Fully unprotected outdoor use

## Product information:

---

The ARCHI8x delivers powerful and immersive low frequency performance in a compact architectural design, purpose built for demanding outdoor and indoor applications. With a low frequency extension down to 36 Hz without processing and doubled program power compared to NOBA8, ARCHI8x offers precise and controlled sub performance with minimal visual impact.

At its core, a tailor made high excursion 8 inch aluminum driver is paired with a vibration cancelling 10 inch aluminum passive radiator. This combination ensures deep, accurate bass while minimizing resonance and structural vibration. The vibration decoupled mounting system further isolates the enclosure from surrounding surfaces, preserving clarity even at high output levels.

Built with a MarineGrade aluminum housing, the ARCHI8x is designed for fully unprotected outdoor use. Flexible ceiling and wall mounting options make it easy to integrate into architectural environments where discretion, durability, and performance are equally critical.

## Applications:

---

- Bars & Restaurants
- Hotels
- Residential



## Properties:

---

 Weatherproof

## Impedance:

---

$\Omega$  8 Ohm

## Usage:



Indoor



Outdoor

## System specifications:

|                           |                                 |                    |
|---------------------------|---------------------------------|--------------------|
| Speaker type              | 8" Bass reflex cabinet          |                    |
| Continuous power (AES)    | 250 W                           |                    |
| Program power handling    | 500 W                           |                    |
| Peak power handling       | 1000 W                          |                    |
| Impedance                 | 8 $\Omega$                      |                    |
| Max SPL (Continuous/AES)  | 115 dB                          |                    |
| Sensitivity (1W/1m)       | 91 dB                           |                    |
| Frequency                 | Range (-10 dB)                  | 36 Hz - 250 Hz     |
| Connectors                | Terminal block with linkthrough |                    |
| Drivers                   | 8" woofer                       |                    |
|                           | 10" passive radiator            |                    |
|                           | Cone material                   | Anodized Aluminium |
| Ingress Protection rating | IPTBA                           |                    |

## Product Features:

|                       |   |
|-----------------------|---|
| Dimensions            | 25.79 x 6.71 x 15.079 " (W x H x D) (Incl. feet & mounting bracket) |
| Weight                | 25.29 lb  |
| Operating temperature | -20 °C ~ 70 °C  |
| Construction          | Aluminium with plastic side covers                                  |
| Mounting & handling   | Vibration-decoupled mounting system                                 |
| Colours               | Black & White   |

## Variants:

- ARCHI8X/B - Black version
- ARCHI8X/W - White version